

## UNICLASS 4-port Rackmountable KVM Switch



**Model : 12001452**

Manufacturer :

This UKV-1480 PS/2 KVM Switch is designed for computer/server management on a centralized single admin desk in corporate, factory as well as in campus computing environment. It also features a hot-plugging capability that allows you to plug off and on the KVM cabling without powering down a whole rack of servers, especially convenient when you are working on a sever rack.

Features 4-port 19" Rackmount PS/2 KVM Switch in metal enclosure PS/2 style keyboard and mouse control Support Microsoft IntelliMouse®, IntelliMouse Explorer®, Logitech NetMouse® and other compatibles Direct channel selection and operation using Front-panel push buttons and keyboard hotkeys Support for DOS, Windows 95/98/SE/ME/2000/XP, Linux, etc. Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs Mouse reset hotkey for non-PnP OS such as Win NT 4.0 and Linux LED indicators for easy port status monitoring Plug-and-play, no Windows driver software needed for PS/2 keyboard and PS/2 operation Buzzer sound for port switching confirmation Autoscan mode for quick browsing of all connected computers Autoscan delay time programmable 5 ~ 100 seconds through hotkey commands High VGA resolution 1920 x 1440 19" rack mount design with metal enclosure for best shielding and protection

Specifications Model No. : UKV-1480 PC Connections : 4 Console Connections :

1 PC Port Connectors : 4 x PS/2 Keyboard 6-pin Mini Din female

4 x PS/2 Mouse 6-pin Mini Din female

4 x VGA HDB 15-pin

female Console Port Connectors : 1 x PS/2 Keyboard 6-pin Mini Din female

1 x PS/2 Mouse 6-pin Mini Din female

1

x VGA HDB 15-pin female PC selection : Hotkeys / Push buttons On Screen

Display : No PC port LED : 8 Scan delay time : 5~100 sec. programmable

through hotkey Keyboard/Mouse emulation : PS/2 VGA Resolution : 1920 x 1440

Power Type : PS/2 interface power Power Adapter : (Optional) DC 9V 1A

Operation Temperature : 0 ~ 40°C Storage Temperature : - 20 ~ 60°C Humidity :

0~90% RH, non-condensing Size : Standard 19" rack mount Housing : Metal

enclosure Dimension (L x W x H) : 220 x 100 x 44.5 mm Weight : 1000 g Safety /

Emission : FCC, CE

Price : \$87.95

Availability: This product was added to our catalog on Monday, 14 May 2007